

FLOPOWER®

Napsak Sprayer



Tank Capacity	± 16 litres
Battery	12V 8.0 Amp/Hour Sealed Lead/Acid
Charger	Automatic Sealed Lead Acid 220V 50HZ Input, 12v 1,000Ma Output
Motor	12V 2.0A
Pump	FLOPOWER FL2207 Flow rate: 2.6L/MIN Flow rate: L.P.N Double Head (supplied) Single Head (supplied) 02: ±3 Bar – 0.8 L/Min 03: ±2.8Bar – 1.1 L/Min 04: ±2 Bar – 1.3 L/Min 06: ±1.5 Bar – 1.6 L/Min Automatic Pressure Switch 80Psi
Pump Materials	Polyethylene Motor Body/Nylon66 Pump body/ VITON Valve
Duty Cycle	Intermittent
Usage time when fully charged	≥5 Hours (Accumulative time)
Spray Nozzle	Polyethylene Nozzle
Inlet Strainer	Polyethylene
Inner Strainer	Stainless Steel
Dimension	41 x 21 x 54.5 cm

Rudd PRODUCTS

Bush Willows, 24 Begonia Road / PO Box 30804

KYALAMI AH 1684

Tel 086 111 4634 / Fax 086 515 9927

Email rudd@rudd.co.za / Website www.rudd.co.za